

| Technical characteristics | |
|-----------------------------------|--|
| Approvals | CE Marking according to EN443:2008 "Helmets for fire-fighting in buildings and other structures" Type A Half coverage shell Optional requirements: /-10 °C (*) -Low temperatures/E1-Conductive headform(metal) |
| Weight | 1150g |
| Size | 52-64 cm |
| Material (shell) | Fiber Reinforced Plastics,FRP |
| Material (shock absorption liner) | modified-Polyphenyleneether : UL-94 V-0 |
| Material (inner cover、Chinstrap) | Flame resistant, inner cover and chinstrap covers, made of aramid |
| material (face shield) | Polycarbonate |
| Face shield approvals | CE marking according to EN14458:2004 "High performance visors" - Face guard ☺ Optional requirements/Use for Fire-fighting/N - Antifog/K - Antiscratch/Ω - Electrical properties (Surface insulation) |

- The fire helmet pictured in this brochure include some special specifications and optional accessories.
for details,please check the individual specifications.
- For the improvement of our products,specifications may change without prior notification.



Fire Helmet
FKT-1402^{EN}

Funayama fire helmet are created in pursuit of a particular form of perfection,
embodying the latest technology, but also an aesthetic sensibility.



- A calculated design based on weight distribution
- Succeeded in developing a light weight helmet weighing only 1,150 grams



- Available to choose either the round cover type or rear cover type of neck curtains that totally seals the face shield
- Side parts to fix the headlight band are added as standard equipment



- Color variations available for use in identifying separate troops



Pearl White



Super Silver



Flush Yellow



Super Gold



Gun Metallic



Blaze Red




Blaze Blue



Blaze Orange

Safety

- CE Marking according to EN443:2008
“Helmets for fire-fighting in buildings and other structures” Type A Half coverage shell
Optional requirements:
/-10 °C (*) -Low temperatures/E1-Conductive headform (metal)



Matching

- A helmet that fits well, designed to be consistent with breathing protection systems of other companies.



Performance

- Ergonomic Wheel ratchet adjustment, Large knob with easy access



Design

- Designed with rain grooves so water does not flow on to the face
- Designed so that the back of the helmet and the cylinder of the breathing apparatus do not easily come in contact



Operating

- Face shield allows for quick opening and closing maneuvers



Comfort

- The face shield provides wider viewing angle
- The face shield filters out 99% ultraviolet rays and has anti-fog and hard coating with a mirror finish

